

# HST - HEAT SOAK TEST

HST

MOD	 MAX B (A x B) mm in	 mm in	Kg lb	kW		 C B (B x A x C) mm in
260/400	2600x4000 102x157	2,8 ÷ 25 .110 ÷ 1	5000 11000	250	2/3 h.	6880x3000x3795 217x118x149
260/520	2600x5200 102x205	2,8 ÷ 25 .110 ÷ 1	5000 11000	250	2/3 h.	6880x3000x3795 217x118x149
321/680	3210x6800 126x268	2,8 ÷ 25 .110 ÷ 1	8000 17600	320	2/3 h.	8410x3000x5510 331x118x217
321/800	3210x8000 126x315	2,8 ÷ 25 .110 ÷ 1	10000 22000	435	2/3 h.	9600x3000x5510 378x118x217

HST SIMPLEX

MOD	 MAX B (A x B) mm in	 mm in	Kg lb	kW		 C B (B x A x C) mm in
260/520	2600x5200 102x205	2,8 ÷ 25 .110 ÷ 1	5000 11000	150	5 h.	6880x3000x3795 217x118x149
321/680	3210x6800 126x268	2,8 ÷ 25 .110 ÷ 1	8000 17600	220	5 h.	8410x3000x5510 331x118x217