

**TMF 55 - TMF 55E**

Front single-head cutting-off machine with automatic blade feed and ample cutting capacity. Pneumatically-controlled head tilting with three fixed positions  $-45^{\circ}$   $90^{\circ}$   $+45^{\circ}$ , internal and external angles up to  $20^{\circ}$  with manual positioning or electronic positioning in "E" version. Pneumatically-operated working area full protection. Hardened-steel worktop. Forward movement on ball-bearing guides and runners. Blade rotation movement with tapered bearings. Horizontal pneumatic clamps with low-pressure device. Hydraulic forward speed adjustment. Blade feed simultaneous two-hand device. Digital LED display screen for showing head tilting. Pull-out shavings drawer. Ready for fitting fume extraction. Micro-mist pneumatic blade lubrication (emulsified oil).

# TMF 55 - TMF 55E

# Rinaldi



<b>Technical details</b>	Three-phase power supply	380/400 - 50/60	Volt-Hz
	Blade rotation speed	2.2	rpm
	Blade	550	mm
	Adjustable vertical support	0...-100	mm
	Blade tilting degrees	-20...+20	°
	Weight	500	kg

<b>Fittings</b>	Service spanner bag
	Operator's and maintenance manual with EC declaration
	Blade Ø 550 mm
	Extraction fan connection Ø 70 mm
	Adjustable levelling feet
	Air blowing gun for cleaning

<b>Accessories</b>	Pneumatic horizontal clamp
	Pneumatic tool lubrication
	Loading roller conveyor
	Unloading roller conveyor